





Bravo 300

Electrical submersible slurry pump



60 Hz	Bravo 300
Discharge connection E	4"
Rated power P_2	7.5 kW / 10 hp
Max. power consumption P_1	8.9 kW
Shaft speed	1735
Rated current at 230V	25 A
Rated current at 460V	13 A
Rated current at 575V	10 A
Solids passage	50 mm
Dimensions A / B / C / D	760 / 460 / 440 / 157 mm
Dimensions A / B / C / D	30 / 18 / 17½ / 6"
Weight	157 kg / 346 lbs

Other voltages on request



ISO 9906/A

General description

Submersible pump for pumping water containing abrasive particles, ground water, slurries

Classification

Electrical submersible slurry pump
Protection class: IP 68

Electrical motor

Squirrel cage induction motor
Insulation class: H (IEC 85), DOL or star/delta

Motor protection

Thermoswitches in motor windings

This pump must be used with external motor protection in accordance with technical data

Cable - SubCab 20 m (66 ft)

DOL: 4x2.5mm² + 2x1.5mm²

Y/D: 7x2.5mm² + 2x1.5mm²

Shaft seals

Double mechanical seal running in an oil compartment
Material lower seal: tungsten carbide - tungsten carbide
Material upper seal: tungsten carbide - aluminium oxide

Materials

Drive unit: *Cast iron*
Pump housing: *Cast iron*
Impeller: *Hard-Iron™*
Discharge connection: *Cast iron*
Wear plate: *Nitrile rubber*
Lifting handle: *Galvanized steel*
Shaft: *Stainless steel*
Studs, screws and nuts: *Stainless steel*
O-rings: *Nitrile rubber*

Limitations

Max. submersion depth: 20 m (66 ft)
Max. liquid temperature: 40 °C (104 °F)
Allowed pH range: 5.5 - 14

Specifications can be changed without notice